

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : B65D 19/34</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/61330</p> <p>(43) International Publication Date: 2 December 1999 (02.12.99)</p>
<p>(21) International Application Number: PCT/SE99/00792</p> <p>(22) International Filing Date: 11 May 1999 (11.05.99)</p> <p>(30) Priority Data: 9801709-8 14 May 1998 (14.05.98) SE</p> <p>(71)(72) Applicant and Inventor: STERNHAMN, Nils-Åke [SE/SE]; Leksbergsvägen 41, S-542 44 Mariestad (SE).</p> <p>(74) Agent: KRANSELL & WENNBORG AB; P.O. Box 27834, S-115 93 Stockholm (SE).</p>		<p>(81) Designated States: CA, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Swedish).</i></p>

(54) Title: PALLET AND METHOD OF MANUFACTURING THE PALLET

(57) Abstract

The invention relates to a pallet arrangement (1), preferably to a pallet intended for one-time use only, comprising an upper deck plate (2), bottom runners (3) and spacer elements (4) located between the deck plate (2) and the bottom runners (3) and functioning as pallet feet. The spacer elements are comprised of supportive tubular elements (5) which are fixed in position relative to the deck plate (2) against locking flaps (8) that are folded down around circular fold lines (7) punched in the deck plate. In turn, the locking flaps (8) are firmly clamped between the tubular spacer elements (5) and locking tubes (10) that are inserted from above through openings (9) that were formed in the deck plate (2) by folding down the locking flaps (8). The invention also relates to a method of manufacturing the pallet, in which method attachment of the spacer elements (4) to the underside of the deck plate (2) is achieved by punching out in said deck plate openings (9) such as to form locking flaps (8) over which the tubular spacer elements (5) are fixed with the aid of locking tubes (10) which are pressed into the openings (9) and which firmly press the tubular spacer elements (5) against said locking flaps (8), whereafter the free ends (11) of the tubular spacer elements are glued firmly to the bottom runners (3).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						